

# Plaza 3-Stone Combo 641

Plaza 3-Stone is a timeless paving stone with an impressionistic embossed surface profile. It creates a gentle and warm effect by combining the soft curved edges of the rectangular and square stones. Plaza 3-Stone Combo is available in many colors and in standard or Heritage™ Series (tumbled) finish to accommodate the most discriminating tastes and desires. Plaza 3-Stone uses large-scale patterns to create interest and drama to commercial landscaping, while the stone's texture and pattern harmonize with surrounding buildings and site furnishings. The Plaza 3-stone combination increases installation efficiencies by delivering three stone shapes on each

## **COMPOSITION AND MANUFACTURE**

Plaza 3-Stone Combo is made from a "no slump" concrete mix. Made under extreme pressure and high frequency vibrations, Plaza 3-Stone Combo has a compressive strength greater than 8000psi, a water absorption maximum of 5% and will meet or exceed ASTM C-936.

#### INSTALLATION

- 1. Excavate unsuitable, unstable or unconsolidated subgrade material and compact the area which has been cleared. Backfill and level with dense graded aggregate suitable for base material. Typically the base material is 4 in. to 8 in. (101mm to 202mm) in depth of compacted base for light vehicular and pedestrian traffic or as otherwise directed by Site Engineer/Architect/Landscape Architect.
- 2. Place bedding course of washed sand conforming to the grading requirements of ASTM C-33 to a uniform depth of 1-1 1/2 in. (25-38mm) screeded to the grade and profile required.
- 3. Install Plaza 3-Stone Combo with vertical side joints approximately 1/8 in. (3mm) in width.
- 4. Where required, cut pavers with an approved cutting device to fit accurately, neatly and without damaged edges.
- 5. Tamp pavers with a plate compactor, uniformly level, true to grade and free of movement.
- 6. Spread sand to 1/8 in. thickness over entire paving area. Stabilization of jointing sand may be required.
- 7. Make one more pass with plate compactor to fill joints with sand.

Complete installation & specification details are available by contacting your Pavestone Company Sales Representative.

Note: Colors are shown as accurately as possible in brochures & samples, but due to the nature of the product, regional color differences and variables in print reproduction, colors may not match exactly. For best results in maintaining color consistency, pavers must be installed from several cubes at a time. Efflorescence, a whitish, powder-like deposit, may appear on concrete pavers. This is a natural occurrence in any concrete product and will usually wear off over time.

#### **APPLICATIONS**

Patios • Entrance Areas • Sidewalks • Terraces • Garden Pathways Pool Decks • Beach Promenades • Pedestrian Malls Roof Gardens Courtyards • Plazas • Driveways • Medians

### PRODUCT INFORMATION

Plaza 3-Stone Combo 641 is available in a thickness of 2 3/8"\* = 60mm







Plaza 3-Stone Combo 641 Large Rectangle, Square, Small Rectangle (Bundled Together)

Nominal Dimensions: Large Rec.: 5 7/16" W x 8 3/16" L 138mm x 208mm

5 7/16" W x 5 7/16" L 138mm x 138mm Small Rec.: 2 11/16" W x 5 7/16" L 68mm x 138mm

Height/Thickness: 60mm = 2 3/8"

Stones/Pallet: 180 Large Rectangles


180 Squares

120 Small Rectangles


Approx. Wt./Pallet: 2,971 lbs.\*\* Sq. ft./Pallet: Product Number: 641 641T (Heritage™ Series)

Fractional dimensions are nominal.

- \* Not available in all markets
- \*\* Does NOT included 50 lbs. for wooden Pallet.



# INSTALLATION PATTERNS





Runner Bond

Random





www.pavestone.com

Atlanta, GA:

Austin/San Antonio, TX:

· Cartersville, GA • Charlotte, NC:

• Colorado Springs, CO:

· Denver. CO:

Houston, TX:

. Dallas/Ft. Worth, TX:

(704) 588-4747 (719) 322-0101 (817) 481-5802 (303) 287-3700 (281) 391-7283

(770) 306-9691

(512) 558-7283

(770) 607-3345

 Kansas City, MO: Las Vegas, NV: · New Orleans, LA:

Phoenix. AZ:

Cape Girardeau, MO: Sacramento/

(573) 332-8312 (530) 795-4400

(816) 524-9900

(702) 221-2700

(985) 882-9111

(602) 257-4588

9/