



AVAILABLE IN GRAY & TAN



Prevents Sand Loss & Joint Erosion
Inhibits Weed Growth • Deters Ants & Insects

* Covers Up to 100 Sq. Ft.

* Coverage applies to standard paver joint width

NET WT 50LB (22.68KG)

SCAN FOR MORE INFO



PolySand™

Premium Polymeric Jointing Sand

PolySand™ is a precise mixture of polymer binders and clean natural sand. PolySand™ will bond with the pavers / stones adding strength to the joint, as well as, reliability to the pavement system. It is ideal for use on any paver surface such as sloping areas, driveways, patios, pool decks, sidewalks, etc.

DIRECTIONS FOR USE

New Construction:

First, the pavers / stones must be installed and properly compacted. For best results with PolySand™, install pavers / stones in accordance to ICPI standards. THE TOP SURFACE OF PAVERS MUST BE COMPLETELY DRY. DO NOT APPLY POLYSAND™ WITH RAIN IN THE FORECAST WITHIN 8 HOURS OF INSTALLATION. TEMPERATURE MUST BE ABOVE 32 DEGREES. This will ensure proper activation of PolySand™.

1. Sweep PolySand™ between the paver / stone joints and compact.
2. Continue to sweep additional PolySand™ until the joints are completely filled to about 1/8 inch below the top of the pavers/stones.
3. Remove all remaining PolySand™ from the paver / stone surface. For best results, a leaf blower is recommended for blowing off excess dust.
4. Direct a fine mist of water in the air so it will gently land on the paver/stone area for 10 to 20 seconds. MUST BE A FINE MIST OF WATER. OVERWATERING WILL ALLOW FOR SEPARATION OF THE POLYMER AND IMPROPER ACTIVATION.
5. Wait 10 to 15 minutes and repeat with a fine mist of water until the joint is completely wetted, about another 10 - 20 seconds. Repeat this step once more if necessary. Avoid overwatering.
6. It is recommended to NOT walk or drive on the pavers/stones for a minimum of 4 hours after installation.
7. PolySand™ will completely cure within 24 - 36 hours, depending on weather conditions.
8. For best results, minimum joint depth of 1.5 inches is recommended.

Existing Construction:

1. Remove all the existing joint filling material from between the pavers / stones. A pressure washer is suggested.
2. Clean off the pavers/stones so they do not have any existing joint filling material on them.
3. Once this is completed, WAIT FOR THE PAVERS / STONES TO COMPLETELY DRY and then follow the instructions on New Paver Installation.




1. SWEEP



2. BLOW



3. SPRAY



4. ENJOY

APPLICATIONS:


Driveways • Patios • Walkways • Pool Decks

Works with Concrete Pavers, Brick Pavers, Patio Pavers, Flagstone, & Limestone

- **Saves Time** - Sweeps easily into joints
- **High Quality** - Remains firm and intact over time
- **Exceptional Performance** - Highly durable
- **Saves Money** - Reduces need for maintenance on replacing sand & weed removal

SAND COVERAGE:

- **Narrow Joints:** 50 lbs. will cover up to 100 sq. ft.
- **Medium Joints:** 50 lbs. will cover 50-75 sq. ft.
- **Wide Joints:** 50 lbs. will cover up to 25 sq. ft.



PAVESTONE®

Creating Beautiful Landscapes™

www.pavestone.com

• Atlanta, GA: (770) 306-9691
• Austin/San Antonio, TX: (512) 558-7283
• Boston, MA: (508) 947-6001
• Cartersville, GA: (770) 607-3345
• Charlotte, NC: (704) 588-4747
• Cincinnati, OH: (513) 474-3783
• Colorado Springs, CO: (719) 322-0101
• Dallas/Ft. Worth, TX: (817) 481-5802
• Denver, CO: (303) 287-3700
• Hagerstown, MD: (240) 420-3780

(770) 306-9691
(512) 558-7283
(508) 947-6001
(770) 607-3345
(704) 588-4747
(513) 474-3783
(719) 322-0101
(817) 481-5802
(303) 287-3700
(240) 420-3780

• Houston, TX: (281) 391-7283
• Kansas City, MO: (816) 524-9900
• Las Vegas, NV: (702) 221-2700
• New Orleans, LA: (985) 882-9111
• Phoenix, AZ: (602) 257-4588
• St. Louis/ Cape Girardeau, MO: (573) 332-8312
• Sacramento/ Winters, CA: (530) 795-4400

(281) 391-7283
(816) 524-9900
(702) 221-2700
(985) 882-9111
(602) 257-4588
(573) 332-8312
(530) 795-4400

PLEASE CHECK WITH A PAVESTONE REPRESENTATIVE FOR AVAILABILITY.

© 2012 Pavestone, L.L.C. All Rights Reserved. PAVESTONE®, Creating Beautiful Landscapes™, and PolySand™ are trademarks of Pavestone, LLC.



World Wide  Pavers

 ICPI Charter Member

